

2.1.3. FREE CHLORINE AUTOMATIC MEASURE STATION.

REF: EST-AUT- CLORO.

2.1.3. 1 0-10 PPM CHLORINE-ELECTRODE OPTION

- **Chlorine measure pump, flow proportional to the free chlorine average**, flow manually adjustable, with level control and accessories (filter with retention double ball valve, injection pipe with double ball check valve, 2m of PVP-glass suction pipes, 4m of polyethylene impulsion pipes, fixation king pin, fusible, etc.).
- **Combination electrode-REDOX** with cable having a length of 0.80m.
- **Combination electrode-pH** with cable having a length of 0.80m.
-
- **Shunt probe-holder/flow-switch** warning if the stand-by control is necessary.
- **5" filter** with 100 PP micro cartridges.
- **Assembly on STRUCTURE.**
- **REDOX and pH buffer solution.**

- Free chlorine **amperometric probe**. Ideal for flow sensor.
- **Shunt probe-holder/methacrylate** with flow regulation.
- **Flow sensor** (proximate sensor)
- **5" filter** with 100 PP micro cartridges.
- **Assembly on STRUCTURE.**

REF.	ROW
<u>EST-AUT- CLORO-1</u>	0.00 – 10.00 mg/l

2.1.3.2 0 - 2 PPM CHLORINE- ELECTRODE OPTION

- **Chlorine measure pump, flow proportional to the free chlorine average**, flow manually adjustable, with level control and accessories (filter with retention double ball valve, injection pipe with double ball check valve, 2m of PVP-glass suction pipes, 4m of polyethylene impulsion pipes, fixation king pin, fusible, etc.).
- Free chlorine **amperometric probe**. Ideal for flow sensor.
- **Shunt probe-holder/methacrylate** with flow regulation.
- Flow sensor (proximate sensor)
- **5" filter** with 100 PP micro cartridges.
- **Assembly on STRUCTURE.**

REF.	ROW
<u>EST-AUT- CLORO-2</u>	0.00 – 2.00 mg/l

2.1.3.3 0 - 2 PPM CHLORINE-ELECTRODES OPTION WITH PH COMPENSATION

- **Chlorine measure pump, flow proportional to the free chlorine average**, flow manually adjustable, with level control and accessories (filter with retention double ball valve, injection pipe with double ball check valve, 2m of PVP-glass suction pipes, 4m of polyethylene impulsion pipes, fixation king pin, fusible, etc.).
- Free chlorine **amperometric probe**. Ideal for flow sensor.
- **Shunt probe-holder/methacrylate** with flow regulation.
- Flow sensor (proximate sensor)
- **5” filter** with 100 PP micro cartridges.
- **Assembly on STRUCTURE.**

REF.	ROW
<u>EST-AUT- CLORO-3</u>	0.00 – 2.00 mg/l