

2.1.4. FREE CHLORINE - PH AUTOMATIC MEASURE STATION. REF: EST-AUT- CLORO -PH.

2.1.4.1 CHLORINE 0 – 10 MG/L MEASURE PUMPS IN ONE CARCASS OPTION

- **Acid and chlorine measure pump, flow proportional to the pH and the chlorine average**, flow manually adjustable, LCD display for a 0 to 10mg/l and a 0 to 14pH reading, with level control and accessories (filter with retention double ball valve, injection pipe with double ball check valve, 2m of PVP-glass suction pipes, 4m of polyethylene impulsion pipes, fixation king pin, fusible, etc.).
- **2 works mode:** acid and chlorine independent mix or acid and chlorine mix with a pH regulation priority.
- **Free chlorine amperometric probe.** Ideal for flow sensor.
- **Combination electrode-pH** with cable having a length of 0.80m.
- **Shunt probe-holder/methacrylate** with flow regulation.
- **Flow sensor** (proximate sensor)
- **5” filter** with 100 PP micro cartridges.
- **Assembly on STRUCTURE.**
- **pH buffer solution.**

REF.	ROW
<u>EST-AUT- CLORO-pH-1</u>	0.00 – 10.00 mg/l 0 – 14 pH

2.1.4.2 0 – 2 MG/L CHLORINE MEASURE PUMPS IN ONE CARCASS OPTION

- **Acid and chlorine measure pump, flow proportional to the pH and the chlorine average**, flow manually adjustable, LCD display for a 0 to 10mg/l and a 0 to 14pH reading, with level control and accessories (filter with retention double ball valve, injection pipe with double ball check valve, 2m of PVP-glass suction pipes, 4m of polyethylene impulsion pipes, fixation king pin, fusible, etc.).
- **2 works mode:** acid and chlorine independent mix or acid and chlorine mix with a pH regulation priority.
- **Free chlorine amperometric probe.** Ideal for flow sensor.
- **Combination electrode-pH** with cable having a length of 0.80m.
- **Shunt probe-holder/methacrylate** with flow regulation.
- **Flow sensor** (proximate sensor)
- **5” filter** with 100 PP micro cartridges.
- **Assembly on STRUCTURE.**
- **pH buffer solution.**

REF.	ROW
<u>EST-AUT- CLORO-pH-2</u>	0.00 – 2.00 mg/l 0 – 14 pH