

2.1.5. FREE CHLORINE (DIGITAL) AUTOMATIC MEASURE STATION.

REF: EST-AUT- CLORO DIGITAL.

2.1.5.1 0 - 10 PPM CHLORINE-ELECTRODE OPTION

- **Free chlorine regulator** with graphic LCD display, measure from 0 to 30 mg/l, on/off or time-switch proportionally instruction point.
- **Chlorine measure pump, flow proportional to the analogical/digital signal free chlorine average**, flow manually adjustable, with level control and accessories (filter with retention double ball valve, injection pipe with double ball check valve, 2m of PVP-glass suction pipes, 4m of polyethylene impulsion pipes, fixation king pin, fusible, etc.).
- Free chlorine **amperometric probe**. Ideal for flow sensor.
- **Shunt probe-holder/methacrylate** with flow regulation.
- **Flow sensor** (proximate sensor)
- **5" filter** with 100 PP micro cartridges.
- **Assembly on STRUCTURE.**

REF.	ROW
<u>EST-AUT- CLORO DIGITAL-1</u>	0.00 – 10.00 mg/l

2.1.5.2 0 - 5 PPM CHLORINE ELECTRODE OPTION

- **Free chlorine** regulator with graphic LCD display, measure from 0 to 30 mg/l, on/off or time-switch proportionally instruction point.
- **Chlorine measure pump, flow proportional to the analogical/digital signal**, flow manually adjustable, with level control and accessories (filter with retention double ball valve, injection pipe with double ball check valve, 2m of PVP-glass suction pipes, 4m of polyethylene impulsion pipes, fixation king pin, fusible, etc.).
- Free chlorine **amperometric probe**. Ideal for flow sensor.
- **Shunt probe-holder/methacrylate** with flow regulation.
- **Flow sensor** (proximate sensor)
- **5" filter** with 100 PP micro cartridges.
- **Assembly on STRUCTURE.**

REF.	ROW
<u>EST-AUT- CLORO DIGITAL-2</u>	0.00 – 5.00 mg/l

2.1.5.3 0 - 5 PPM CHLORINE ELECTRODE OPTION WITH PH COMPENSATION

- **Free chlorine** regulator with graphic LCD display, measure from 0 to 30 mg/l, on/off or time-switch proportionally instruction point.
- **Chlorine measure pump, flow proportional to the analogical/digital signal**, flow manually adjustable, with level control and accessories (filter with retention double ball valve, injection pipe with double ball check valve, 2m of PVP-glass suction pipes, 4m of polyethylene impulsion pipes, fixation king pin, fusible, etc.).
- Free chlorine **amperometric probe with pH compensation**. Ideal for flow sensor.
- **Shunt probe-holder/methacrylate** with flow regulation.
- **Flow sensor** (proximate sensor)
- **5" filter** with 100 PP micro cartridges.
- **Assembly on STRUCTURE**.

REF.	ROW
<u>EST-AUT- CLORO DIGITAL-3</u>	0.00 – 5.00 mg/l