

**BRIDLES WITH CONNECTOR BRIDLES-CARRIER PVC-U AND PVC-U BRIDLE.
BRIDLE SYSTEM IN 1452
MODEL: BRIDA**
Function:

Kit composed with a bridle holder cylindrical cover, idle bridle and pipe to connect tanks to the extern pipes.

Characteristics:

- Dimensioned according to EN 1452-2 and 1452-3 norms for pipe standard connexion.
- Plastic matter PVC-U and Steel galvanized matter.



DN	D [mm]	PN [mm]	H [mm]	Z [mm]	E [mm]	K [mm]	F [mm]
15	20	16	20	4	95	65	14x4
20	25	16	23	4	105	75	14x4
25	32	16	26	4	115	85	14x4
32	40	16	30	4	142	100	18x4
40	50	16	35	4	152	110	18x4
50	63	16	42	4	165	125	18x4
65	75	16	47	3	185	145	18x4
80	90	16	56	5	200	160	18x8
100	110	16	66	5	220	180	18x8
110	140 x 125	16	74	5	230	190	18x8
110	125	16	74	5	250	210	18x8
125	140	16	81	5	250	210	18x8
150	160	10	91	5	285	240	22x8
175	200	10	112	6	315	270	22x8
200	225	10	125	6	340	295	22x8
225	250	10	125	6	399	350	22x12
300	315	10	125	6	450	400	22x12